

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Silirub AS

Revision: 25/04/2016

Page 1 from 3

Reference nr DOP: 230777

Unique identification code of the product type:

Soudal Silirub AS

Intended use or uses of the construction product:

Sealants used for sanitary applications.

Construction product in accordance with applicable harmonised specifications:

EN 15651-3:2012: Type S: CLASS S1

System or systems of assesment and verification of consistency of performance of the construction product, as set out in Annex V:

System 3: for essential characteristics

System 4: for reaction to fire

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

The notified body:

IFT Rosenheim GmbH, NB 0757 has carried out Determination of the Product Type under system 3.

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Silirub AS

Revision: 25/04/2016

Page 2 from 3

Declared Performance: EN 15651-3:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class F	EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Microbiological growth	0	
Durability	Pass	

Conditioning:

Method A

Test substrate:

Aluminium

Glass

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager
BE-2300 Turnhout, 25/04/2016

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 25/04/2016

Page 3 from 3



NB 0757

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

14

Reference nr DOP: 230777

EN 15651-3: 2012

Sealants used for sanitary applications.

Soudal Silirub AS

EN 15651-3:2012: Type S: CLASS S1

Conditioning:
Method A
Substrate:
Aluminium
Glass

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class F	EN 15651-3: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Elongation at break	≥ 25%	
Microbiological growth	0	
Durability	Pass	